



Dimensions: 121(D)x75(W)x110(H) mm

AD2150F Series

150Watts, Dual independent Output

Features

- High power density
- Convection cooled
- RoHS compliance
- 3 year warranty
- Great reliability
- DIN Rail / Wall bracket mounting solution
- Over voltage protection
- Overload protection
- Short circuit protection

Safety Standards



EN 60950 (Marking)


EMC Standards

EN55011	Class B
EN55022	Class B
EN61000-4-2	Level 3
EN61000-4-3	Level 3
EN61000-4-4	Level 3
EN61000-4-5	Level 3
EN61000-4-6	Level 3
EN61000-4-8	Level 3
EN61000-4-11	Level 3

Model List

Model	O/P Voltage Adjustment	Min.	Loading Rated	Max.	Ripple Noise	Efficiency	Over Voltage Protection
AD21501F	+12VDC±10% +5VDC -----	0A	11.0A 3.0A	11.0A 3.0A	100mVp-p 60mVp-p	80%	15~17VDC -----
AD21502F	+24VDC±10% +5VDC -----	0A	5.5A 3.0A	5.5A 3.0A	150mVp-p 60mVp-p	82%	27~30VDC -----

Model Encoding




Specification

General		
Switching Frequency		85kHz
Isolation Voltage	Input-Output	3000VAC /4242VDC
	Input-FG	1500VAC/2121VDC
	Output-FG	500VAC/ 710VDC
Isolation Resistance		100MΩ when Input-Output @500VDC
Operating Temperature		-40°C~40°C ambient
Derating		2.5% per degree from 40°C to 60°C
Storage Temperature		-40°C to +85°C
Relative Humidity		5%~95% RH, Non-condensing.
Temperature Coefficient		±0.04% of output voltage per °C
MTBF		60,000hrs Min. Per MIL-HDBK-217F, 25°C GB
Attitude During Operation		2000m
Installation position		Vertical
Vibration		Random Vibration, 10~500Hz. 3 axise
Input		
Input Voltage		100~240VAC/120~370VDC
Input Frequency		47~63Hz
Inrush Current (cold start)		22A/115VAC 44A/230VAC
Rated Input Current		3.5A Max., Vi=100~240VAC
Leakage Current		Input-output 0.25mA, Input-FG 3.5mA, Vi=250VAC
Output		
Output Voltage accuracy		±1%
Minimun Load		0%
Line Regulation		±1%/±1%, measuring from low line to high line rated load
Load Regulation		±3%/±3%, measuring from 20% to 100% of rated load 230VAC input
Voltage Trim Range		±10%
Rated Continuous Loading		See model list
Hold Up Time		20mS Min., Full load@230VAC.
Turn On Time		1300mS
Rise Time		13mS
Fall Time		25mS


Specification

Output		
Transient Response	Recovery Time	2mS, Load change 50% to 100%
	Voltage Deviation	5%, Load change 50% to 100%
Efficiency		See model list, measuring at rated load and 230VAC input
Ripple and Noise		See model list, measuring by using a 0.1 μ F/630V metalize capacitor and a 47 μ F electrolytic capacitor parallel on the test point, at rated load and 230VAC input.
Protection		
Input Fuse		3.15A/250V
Internal Surge Load Protection		Varistor, IEC6100-4-5
Degree of Protection		IP20
Short Circuit Protection		Autorecovery
Over Voltage Protection		Autorecovery
Rated Over Load Protection		160~200%
Overload protection		Power limited

Derating Curve



Mechanical Details




Case No.	AD120	
Dimensions	121(D)x75(W)x110(H)mm	
Case Material	Metal	
Weight	AD21501F	602.6 g
	AD21502F	602.6 g

Terminal Allocation

Designation	Description
DC OK	Green LED Indicator
V Adj.	O/P Voltage adjustment
V ₁	Output Voltage 1
V ₂	Output Voltage 2
Gnd ₁	Ground 1
Gnd ₂	Ground 2
⏏	Earth
N	Input Neutral
L	Input Line

Installation instruction



Place the top of the AD2150F rail mount over the top of the DIN rail. Tilt the bottom of the AD2150F toward the DIN rail until it snaps into place.

To remove the AD2150F from the DIN rail, use a flathead screwdriver to pull down the bottom of the rail mount and tilt it away from the DIN rail.

To install AD2150F on wall/plate, loosening screws on mounting bracket and pull both brackets out first. Then re-screwing the two brackets with screws onto wall/plate.

The left housing of AD2150F is designed as a heat sink, please keeping a minimum distance of 15mm from each other.